

	-	-	f 0.5%	100%
	-	-	f 1.5%	
	-	-	1.0 s	120Vac, 70%-100%
	-	-	0.5 s	220Vac, 70%-100%
	-	0.03%/ C	-	= 0 C ~ Tc

25 C

@120Vac				
EUP-240S105ST				
Io= 700 mA	88.5%	90.5%	-	
Io=1050 mA	87.5%	89.5%	-	
EUP-240S150ST				
Io=1050 mA	88.5%	90.5%	-	
Io=1500 mA	87.5%	89.5%	-	
EUP-240S210ST				100% 25°
Io=1400 mA	88.5%	90.5%	-	
Io=2100 mA	87.0%	89.0%	-	2%
EUP-240S420ST				
Io=2800 mA	87.5%	89.5%	-	
Io=4200 mA	85.5%	87.5%	-	
EUP-240S670ST				
Io=4600 mA	87.0%	89.0%	-	
Io=6700 mA	85.0%	87.0%	-	
@220Vac				
EUP-240S105ST				
Io= 700 mA	91.5%	93.5%	-	
Io=1050 mA	90.0%	92.0%	-	
EUP-240S150ST				
Io=1050 mA	91.5%	93.5%	-	
Io=1500 mA	90.0%	92.0%	-	
EUP-240S210ST				100% 25°
Io=1400 mA	91.5%	93.5%	-	
Io=2100 mA	90.0%	92.0%	-	2%
EUP-240S420ST				
Io=2800 mA	90.5%	92.5%	-	
Io=4200 mA	88.5%	90.5%	-	
EUP-240S670ST				
Io=4600 mA	90.0%	92.0%	-	
Io=6700 mA	88.0%	90.0%	-	

--	--	--	--	--

@277Vac

EUP-240S105ST	Io= 700 mA	92.0%	94.0%	-		
	Io=1050 mA	90.5%	92.5%	-		
EUP-240S150ST	Io=1050 mA	92.0%	94.0%	-		
	Io=1500 mA	90.5%	92.5%	-	100%	5
EUP-240S210ST	Io=1400 mA	92.0%	94.0%	-		
	Io=2100 mA	90.5%	92.5%	-		
EUP-240S420ST	Io=2800 mA	91.0%	93.0%	-		
	Io=4200 mA	89.0%	91.0%	-		
EUP-240S670ST	Io=4600 mA	90.5%	92.5%	-		
	Io=6700 mA	88.5%	90.5%	-		

EMI	
FCC Part 15 ⁽¹⁾	ANSI C63.4 Class B
	This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired Operation.
EMS	
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: line to line 6 kV, line to earth 10 kV ⁽²⁾
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Require

EUP-240S105ST(Io=700mA)

EUP-240S105ST(Io=1050mA)

EUP-240S150ST(lo=1050mA)

EUP-240S150ST(lo=1500mA)

EUP-240S210ST(lo=1400mA)

EUP-240S210ST(lo=2100mA)

EUP-240S420ST(lo=2800mA)

EUP-240S420ST(lo=4200mA)

EUP-240S670ST(Io=4600mA)

EUP-240S670ST(Io=6700mA)

--	--

EUP-240S150ST

				(loset)			
1	2	3	4				I
ON	ON	ON	ON	1500mA	80V	160V	
ON	ON	ON	OFF	1450mA	83V	165V	
ON	ON	OFF	ON	1400mA	86V	171V	
ON	ON	OFF	OFF	1350mA	89V	178V	
ON	OFF	ON	ON	1300mA	93V	185V	
ON	OFF	ON	OFF	1250mA	96V	192V	
ON	OFF	OFF	ON	1200mA	100V	200V	
ON	OFF	OFF	OFF	1150mA	105V	209V	
OFF	ON	ON	ON	1100mA	109V	218V	
OFF	ON	ON	OFF	1050mA	115V	229V	
OFF	ON	OFF	ON	1000mA	120V	229V	
OFF	ON	OFF	OFF	950mA	127V	229V	
OFF	OFF	ON	ON	900mA	134V	229V	

Z EUP-240S210ST

• » f ´				Î Ð Ô W f ´ (loset)	Î Ð Ô 8 ˘		Ô
1	2	3	4	À ¹ š	£ 3 š	£ Ū š	/
ON	ON	ON	ON	2100mA	57V	114V	É ä ˘ ß v — à 8
ON	ON	ON	OFF	2000mA	60V	120V	
ON	ON	OFF	ON	1900mA	63V	126V	
ON	ON	OFF	OFF	1800mA	67V	133V	
ON	OFF	ON	ON	1700mA	71V	141V	
ON	OFF	ON	OFF	1600mA	75V	150V	
ON	OFF	OFF	ON	1500mA	80V	160V	
ON	OFF	OFF	OFF	1400mA	86V	171V	
OFF	ON	ON	ON	1300mA	92V	171V	
OFF	ON	ON	OFF	1200mA	100V	171V	
OFF	ON	OFF	ON	1100mA	109V	171V	
OFF	ON	OFF	OFF	1000mA	120V	171V	

EUP-240S420ST

				(loset)			
1	2	3	4				I
ON	ON	ON	ON	4200mA	29V	57V	
ON	ON	ON	OFF	4000mA	30V	60V	
ON	ON	OFF	ON	3800mA	32V	63V	
ON	ON	OFF	OFF	3600mA	34V	66.5V	
ON	OFF	ON	ON	3400mA	36V	70.5V	
ON	OFF	ON	OFF	3200mA	38V	75V	
ON	OFF	OFF	ON	3000mA	40V	80V	
ON	OFF	OFF	OFF	2800mA	43V	86V	
OFF	ON	ON	ON	2600mA	46V	86V	
OFF	ON	ON	OFF	2400mA	50V	86V	
OFF	ON	OFF	ON	2200mA	55V	86V	
OFF	ON	OFF	OFF	2000mA	60V	86V	

EUP-240S670ST

				(loset)			
1	2	3	4				/
ON	ON	ON	ON	6700mA	18V	36V	
ON	ON	ON	OFF	6400mA	19V	37.5V	
ON	ON	OFF	ON	6100mA	20V	39.5V	

EUP-240SxxxST



